

Amendments to the Specification

Please **revise the paragraph beginning on page 1, line 19 of the specification** as follows:

In a reciprocating compressor of the related art, a crank shaft 3 is rotated at a certain number of revolution by rotating force of the rotor and the stator which are power transmitting components. ~~And, the~~ The rotational motion is converted into reciprocal straight line motion by a sleeve 16 and a connecting rod 17. A piston 19 is fastened to the connecting rod 17, and moves back and forth within the cylinder 7. By ~~rotational~~ back and forth motion of the piston 19, coolant is inhaled through the suction valve 20 and discharged through the discharging valve 26 after being compressed under the high pressure.

Please **revise the paragraph beginning on page 3, line 7 of the specification** as follows:

Also, when the piston 19 moves from the bottom dead point to the top dead point, internal pressure of the cylinder 7 is successively elevated to compress the coolant. When such internal pressure of the cylinder 7 becomes larger than spring force of the discharging valve 26, the ~~discharging~~ discharge valve 26 is opened to form a passage through which the high pressure of the coolant is discharged from the cylinder.

Please **revise the paragraph beginning on page 3, line 12 of the specification** as follows:

As shown above, when the rotor revolves for one time the operation of the suction valve 20 and the discharge valve 26 ~~initiated~~ is initiated and suction and discharge of coolant into and from the cylinder 7 is carried out. When the suction and discharge valves 20 and 26 are closed, the suction and discharge valves 20 and 26 collide into the valve plate 22 thereby generating noise and vibration. The loudness of the collision noise depends on a vibration transmission capability of the valve plate 22.

Please **revise the paragraph beginning on page 7, line 7 of the specification** as follows:

Hereinafter ~~detailed~~ a detailed description ~~will be made about~~ of the embodiments of the invention ~~is provided~~ in reference to ~~FIG. 3~~ FIGS. 3A to FIG. 10, in which some components of the invention are designated with the same reference numerals as those of the related art for the convenience's sake of explanation.

Please **revise the paragraph beginning on page 7, line 16 of the specification** as follows:

As shown in FIG. 4, vibration and noise generated from collision of the suction valve 20 and the ~~discharging~~ discharge valve 26 into the valve plate 22

spreads into all directions about a suction port. Noise and vibration are transmitted to the grooves composed of the number of cavities 118 during a spreading process. The cavities 118 are hollow spaces with various widths and respectively have the resonant frequencies pertinent thereto so that only the pertinent frequencies are resonated in the cavities 118, that is, the cavities 118 obstruct transmission of vibration and noise with the frequencies pertinent to the resonant frequencies to damp the amplitude of vibration and noise.

Please **revise the paragraph beginning on page 7, line 24 of the specification** as follows:

According to such a principle, when the cavities are adjusted in width in correspond to the most problematic bands of vibration and noise generated from collision of the suction and ~~discharging~~ ~~discharge~~ valves 20 and 26 with the valve plate 22.